

HEALTH, SAFETY, AND ENVIRONMENTAL PROCEDURES











COSHH ASSESSMENT

ACTIVITY/PRODUCT TO BE ASSESSED:	SOFT SHEEN EASY RECOAT P/C MEL LAC	REFERENCE:	COSHH 30		
		DATE:	04/02/2021		
ORGANISATION:	Humphrey and Stretton Limited				
DESCRIBE THE ACTIVITY OR WORK PROCESS:	Used to paint fire doors				
LOCATON OF PROCESS BEING CARRIED OUT:	All areas				
IDENTIFY PERSONS AT RISK:	The Operative <input checked="" type="checkbox"/>	Other Employees <input type="checkbox"/>	Other Contractors <input type="checkbox"/>	Any Visitors <input type="checkbox"/>	General Public <input type="checkbox"/>
EUROPEAN CLASSIFICATION (CLP REGS) (Mandatory from 01/06/15)					
Toxic	<input type="checkbox"/>	Corrosive	<input type="checkbox"/>		
Flammable	<input checked="" type="checkbox"/>	Oxidising	<input type="checkbox"/>		
Gas Under Pressure	<input type="checkbox"/>	Danger to Environment	<input checked="" type="checkbox"/>		
Explosive	<input type="checkbox"/>	Caution / Irritant	<input checked="" type="checkbox"/>		
Serious - Long-Term Health Hazard	<input type="checkbox"/>				
TYPE OF HAZARD:	Gas <input type="checkbox"/>	Vapour <input type="checkbox"/>	Mist <input type="checkbox"/>	Fume <input type="checkbox"/>	
	Dust <input type="checkbox"/>	Liquid <input type="checkbox"/>	Solid <input checked="" type="checkbox"/>	Other <input type="checkbox"/>	
STATE THE RISKS TO HEALTH FROM IDENTIFIED HAZARDS:	Harmful by inhalation and with contact with the skin. Risk of serious damage to eyes. Irritating to the skin.				
WORKPLACE EXPOSURE LIMITS (WELS)					
INGREDIENT:	SHORT TERM EXPOSURE LIMIT (15 MINS):	LONG TERM EXPOSURE LEVEL (8 HOUR TWA):			
Acetone	3620 mg/m ³	1210 mg/m ³			
Xylene	441 mg/m ³	220 mg/m ³			

Butanol	154 mg/m ³	Not Set
Ethanol	1920 mg/m ³	Not Set
Butyl Acetate	996 mg/m ³	724 mg/m ³
Isopropyl Alcohol	1250 mg/m ³	999 mg/m ³
Ethylbenzene	552 mg/m ³	441 mg/m ³

PERSONAL PROTECTIVE EQUIPMENT (TYPE AND STANDARD):

	Dust Mask	<input type="checkbox"/>			Visor	<input type="checkbox"/>	
	Respirator	<input checked="" type="checkbox"/>	If exceeding Workplace Exposure Limits a Half Mask respirator with Type A, (EN14387) and particulate filter		Glasses	<input checked="" type="checkbox"/>	Wear Safety Glasses
	Gloves	<input checked="" type="checkbox"/>	Wear PVC Gloves		Overalls	<input checked="" type="checkbox"/>	Wear protective clothing
	Safety Footwear	<input checked="" type="checkbox"/>	Wear safety footwear		Other	<input checked="" type="checkbox"/>	Wash hands after handling.

FIRST AID

ROUTE OF EXPOSURE:	SYMPTOM:	FIRST AID TO BE APPLIED:
EYES	IRRITANT	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 10 minutes, keeping eye lids open.
INGESTION	HARMFUL	If swallowed, seek medical advice immediately and show this container or label keep person warm do not induce vomiting.
INHALATION	HARMFUL	Remove victim to fresh air. Keep person warm and at rest. If not breathing. If breathing is irregular or respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
SKIN	IRRITANT	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser.

PRECAUTIONS TO BE TAKEN WHEN DEALING WITH THE FOLLOWING:							
FIRE	<p>Extinguishing media</p> <p>Use Alcohol resistant foam, carbon dioxide, powders, water spray, do not use water jet.</p> <p>Fire will produce dense black smoke, Exposure to decomposition products may cause a health hazards.</p> <p>Decomposition products may produce the following materials: Carbon Monoxide, Carbon Dioxide, smoke, oxides of nitrogen.</p> <p>Cool closed containers exposed to fire with water. Do not release run off from fire to drains or watercourses.</p> <p>Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.</p>						
DISPOSAL	Dispose correctly in line with environmental legislative requirements.						
SPILLAGE	<p>Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.</p> <p>Contain and collect spillage with non- combustible absorbent material. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local Regulations.</p>						
STORAGE	Store product in a cool well-ventilated area, keep away from direct heat and direct sunlight. Keep away from sources of ignition. Keep containers upright. Keep product away oxidizing agents, strong alkalis, strong acids.						
ADDITIONAL CONTROLS TO BE APPLIED (E.G. EXTRACTION, TRAINING, SUPERVISION ETC.):							
IS EXPOSURE ADEQUATELY CONTROLLED?			YES	<input checked="" type="checkbox"/>	NO	<input type="checkbox"/>	
RISK RATING FOLLOWING CONTROL MEASURES:		High	<input type="checkbox"/>	Medium	<input checked="" type="checkbox"/>	Low	<input type="checkbox"/>
THIS ASSESSMENT CARRIED OUT REVIEWED BY:							
NAME:	Calogero Gattuso	SIGNATURE:	<i>Calogero Gattuso</i>	DATE:	04/02/2021		
CONTROLS CHECKED BY:	Dave Humphrey	SIGNATURE:		DATE:			