

Spindle Moulder

IF THE RISK RATING (RR) IS ABOVE 16 WORK WILL NOT BE ALLOWED TO PROCEED UNTIL CONTROL MEASURES ARE REVIEWED AND REDUCED

Risk Rating (RR) Severity (S) x Probability (P)

Low Risk = 1-8 Medium Risk = 9-15 High Risk 16-25

			Probabil	ity of Incident o	curring	
		Frequent = 5	Likely = 4	Occasional = 3	Seldom = 2	Unlikely = 1
	Fatality = 5	25	20	15	10	5
> =	Major Injury = 4	20	16	12	8	4
Severity Of Harm	Reportable to HSE = 3	15	12	9	6	3
δğ	Minor Injury = 2	10	8	6	4	2
	First Aid applied = 1	5	4	3	2	1

Hazard Identification and Assessment

Site and Location of work:	Hump	hrey & St	tretton - S	Stretton H	EN11 OEU	Risk Assessment No.	RA013			
Brief description of work:	Spindle Moulder				Location:	Factory Area			Risk Assessment Issue No.	Issue 1
Number of Persons at Risk:	EMP	CON	PUB	VIS	Assessed By:	on Site By:		CG/DH/SH	Duration of Task	Varies
(anticipated in each category)	1	0	0	0	Date of Assessment:			24.06.2020 Review Cycle		Where circumstances dictate

CON - Contractor **PUB** – Public VIS - Visitor Code: Persons at Risk **EMP** – Employee Without Controls With Controls Methods of Hazard monitoring Foreseeable Risks Control Measures Hazard RR Ref. RR S Р Р control S SxP No. SxP measures During operation, never put hands or tools in the cutting area. Make sure the machine Exposure to Injuries may be sustained due to exposure of moving parts and is fully isolated before adjusting cutters. 1 moving and Always make sure that the guards are in 3 2 6 rotating cutters. 3 3 place and in working order. parts/cutters



Spindle Moulder

product

IF THE RISK RATING (RR) IS ABOVE 16 WORK WILL NOT BE ALLOWED TO PROCEED UNTIL CONTROL MEASURES ARE REVIEWED AND **REDUCED**

Risk Rating (RR) Severity (S) x Probability (P)

Low Risk = 1-8 Medium Risk = 9-15 High Risk 16-25

			Probabil	ity of Incident or	ccurring	
		Frequent = 5	Likely = 4	Occasional = 3	Seldom = 2	Unlikely = 1
	Fatality = 5	25	20	15	10	5
> =	Major Injury = 4	20	16	12	8	4
Severity Of Harm	Reportable to HSE = 3	15	12	9	6	3
ŏδ	Minor Injury = 2	10	8	6	4	2
	First Aid applied = 1	5	4	3	2	1

Site and Location of work:	Hump	hrey & St	retton - S	Stretton H	EN11 OEU	Risk Assessment No.	RA013				
Brief description of work:	Spindle Moulder				Location:	Factory Area			Risk Assessment Issue No.	Issue 1	
Number of Persons at Risk:	EMP	CON	PUB	VIS	Assessed By:	CG/DH/SH	Assessed on Site By: CG/DH/SH		Duration of Task	Varies	
(anticipated in each category)	1	0	0	0	Date of Assessment:	24.06.2020 Date of Site Assessment		24.06.2020 Review Cycle		Where circumstances dictate	

Code: Persons at Risk **EMP** – Employee **CON** – Contractor **PUB** – Public VIS - Visitor Without Controls With Controls Methods of Hazard monitoring **Control Measures** Foreseeable Risks Ref. Hazard RR RR S Р control S Р SxP No. SxP measures Could sustain splinters when Handling of handling wood. Make sure that suitable gloves are worn at all 2 the timber 2 2 4 2 2 times whilst operating the machine.



Spindle Moulder

IF THE RISK RATING (RR) IS ABOVE 16 WORK WILL NOT BE ALLOWED TO PROCEED UNTIL CONTROL MEASURES ARE REVIEWED AND REDUCED

Risk Rating (RR) Severity (S) x Probability (P)

Low Risk = 1-8 Medium Risk = 9-15 High Risk 16-25

			Probabil	ity of Incident or	ccurring	
		Frequent = 5	Likely = 4	Occasional = 3	Seldom = 2	Unlikely = 1
	Fatality = 5	25	20	15	10	5
> =	Major Injury = 4	20	16	12	8	4
Severity Of Harm	Reportable to HSE = 3	15	12	9	6	3
ŏδ	Minor Injury = 2	10	8	6	4	2
	First Aid applied = 1	5	4	3	2	1

Site and Location of work:	Hump	hrey & St	retton - S	Stretton H	EN11 OEU	Risk Assessment No.	RA013				
Brief description of work:	Spindle Moulder				Location:	Factory Area			Risk Assessment Issue No.	Issue 1	
Number of Persons at Risk:	EMP	CON	PUB	VIS	Assessed By:	CG/DH/SH	Assessed on Site By: CG/DH/SH		Duration of Task	Varies	
(anticipated in each category)	1	0	0	0	Date of Assessment:	24.06.2020 Date of Site Assessment		24.06.2020 Review Cycle		Where circumstances dictate	

Code: Persons at Risk EMP – Employee CON – Contractor PUB – Public VIS – Visitor

Hazard			With	out C	ontrols		Methods of	٧	Vith Co	ontrols
Ref. No.	Hazard	Foreseeable Risks		Р	RR SxP	Control Measures	monitoring control measures	S	Р	RR SxP
3	Slip, Trips & Falls	Slip/fall resulting in an injury.	4	2	8	Make sure that a good standard of housekeeping is in place to minimise the generation of dust/waste. Clean down the inside of the cabinet and dust extraction ports.		4	1	4



Spindle Moulder

IF THE RISK RATING (RR) IS ABOVE 16 WORK WILL NOT BE ALLOWED TO PROCEED UNTIL CONTROL MEASURES ARE REVIEWED AND REDUCED

Risk Rating (RR) Severity (S) x Probability (P)

Low Risk = 1-8 Medium Risk = 9-15 High Risk 16-25

			Probabil	ity of Incident or	ccurring	
		Frequent = 5	Likely = 4	Occasional = 3	Seldom = 2	Unlikely = 1
	Fatality = 5	25	20	15	10	5
> =	Major Injury = 4	20	16	12	8	4
Severity Of Harm	Reportable to HSE = 3	15	12	9	6	3
ŏδ	Minor Injury = 2	10	8	6	4	2
	First Aid applied = 1	5	4	3	2	1

Site and Location of work:	Hump	hrey & St	retton - S	tretton H	EN11 OEU	Risk Assessment No.	RA013			
Brief description of work:	Spindle Moulder				Location:	Factory Area			Risk Assessment Issue No.	Issue 1
Number of Persons at Risk:	EMP	CON	PUB	VIS	Assessed By:	CG/DH/SH	Assessed on Site By:	CG/DH/SH	Duration of Task	Varies
(anticipated in each category)	1	0	0	0	Date of Assessment:	24.06.2020 Date of Site Assessment		24.06.2020 Review Cycle		Where circumstances dictate

Code: Persons at Risk **EMP** – Employee **CON** – Contractor **PUB** – Public VIS - Visitor Without Controls With Controls Methods of Hazard monitoring **Control Measures** Foreseeable Risks Hazard RR RR Ref. S Р control S Ρ SxP No. SxP measures Noise Make sure that hearing protection is being worn at 4 6 3 2 3 3 Potential hearing loss all times whilst operating the machine. Exposure Eye Potential eye injuries due to 5 Eye Protection to be worn whilst operating the 2 2 2 Injuries 2 running of the machine machine



Spindle Moulder

IF THE RISK RATING (RR) IS ABOVE 16 WORK WILL NOT BE ALLOWED TO PROCEED UNTIL CONTROL MEASURES ARE REVIEWED AND REDUCED

Risk Rating (RR) Severity (S) x Probability (P)

Low Risk = 1-8 Medium Risk = 9-15 High Risk 16-25

			Probabil	ity of Incident or	curring	
		Frequent = 5	Likely = 4	Occasional = 3	Seldom = 2	Unlikely = 1
	Fatality = 5	25	20	15	10	5
> =	Major Injury = 4	20	16	12	8	4
Severity Of Harm	Reportable to HSE = 3	15	12	9	6	3
ŏδ	Minor Injury = 2	10	8	6	4	2
	First Aid applied = 1	5	4	3	2	1

Site and Location of work:	Hump	hrey & St	retton - S	tretton H	EN11 OEU	Risk Assessment No.	RA013			
Brief description of work:	Spindle Moulder				Location:	Factory Area			Risk Assessment Issue No.	Issue 1
Number of Persons at Risk:	EMP	CON	PUB	VIS	Assessed By:	CG/DH/SH	Assessed on Site By:	CG/DH/SH	Duration of Task	Varies
(anticipated in each category)	1	0	0	0	Date of Assessment:	24.06.2020 Date of Site Assessment		24.06.2020	Review Cycle	Where circumstances dictate

Code:Persons at RiskEMP - EmployeeCON - ContractorPUB - PublicVIS - Visitor

Hazard			With	out Co	ontrols		Methods of	V	Vith Co	ntrols
Ref. No.	Hazard	Foreseeable Risks	S	Р	RR SxP	Control Measures	monitoring control measures	S	Р	RR SxP
6	Dust Exposure	Respiratory Irritation	3	4	12	Make sure good housekeeping is being maintained. Do not make dust airborne. Make sure the local extraction system is working at the correct rate. This should be checked every 14 months by a competent person.		3	2	6



Spindle Moulder

IF THE RISK RATING (RR) IS ABOVE 16 WORK WILL NOT BE ALLOWED TO PROCEED UNTIL CONTROL MEASURES ARE REVIEWED AND REDUCED

Risk Rating (RR) Severity (S) x Probability (P)

Low Risk = 1-8 Medium Risk = 9-15 High Risk 16-25

		Probability of Incident occurring									
		Frequent = 5	Likely = 4	Occasional = 3	Seldom = 2	Unlikely = 1					
	Fatality = 5	25	20	15	10	5					
>=	Major Injury = 4	20	16	12	8	4					
Severity Of Harm	Reportable to HSE = 3	15	12	9	6	3					
<u>ي</u> ي	Minor Injury = 2	10	8	6	4	2					
	First Aid applied = 1	5	4	3	2	1					

machine. machine in an unsafe matter. permitted to operate said machine



Spindle Moulder

IF THE RISK RATING (RR) IS ABOVE 16 WORK WILL NOT BE ALLOWED TO PROCEED UNTIL CONTROL MEASURES ARE REVIEWED AND REDUCED

Risk Rating (RR) Severity (S) x Probability (P)

Low Risk = 1-8 Medium Risk = 9-15 High Risk 16-25

		Probability of Incident occurring									
		Frequent = 5	Likely = 4	Occasional = 3	Seldom = 2	Unlikely = 1					
	Fatality = 5	25	20	15	10	5					
> =	Major Injury = 4	20	16	12	8	4					
Severity Of Harm	Reportable to HSE = 3	15	12	9	6	3					
<u>ي</u> ي	Minor Injury = 2	10	8	6	4	2					
	First Aid applied = 1	5	4	3	2	1					

8	Entanglement and trapping	Injuries due to being drawn into the machine and jamming	3	4	12	Gloves must NOT be worn when operating this machine. When feeding material into the machine make sure that hands are kept away from any of the moving cutters. Always run the machine at the slowest speed.	3	2	6
9	Entanglement and trapping (cont.)	Injuries due to being drawn into the machine and jamming	4	2	8	Make sure that the machine is kept clear of any off-cuts and is kept clean at all times. Make sure that any long pieces of product that is fed through is done so in a safe manner to prevent jamming.	4	1	4



Spindle Moulder

IF THE RISK RATING (RR) IS ABOVE 16 WORK WILL NOT BE ALLOWED TO PROCEED UNTIL CONTROL MEASURES ARE REVIEWED AND REDUCED

Risk Rating (RR) Severity (S) x Probability (P)

Low Risk = 1-8 Medium Risk = 9-15 High Risk 16-25

		Probability of Incident occurring								
		Frequent = 5	Likely = 4	Occasional = 3	Seldom = 2	Unlikely = 1				
	Fatality = 5	25	20	15	10	5				
> =	Major Injury = 4	20	16	12	8	4				
Severity Of Harm	Reportable to HSE = 3	15	12	9	6	3				
ŏδ	Minor Injury = 2	10	8	6	4	2				
	First Aid applied = 1	5	4	3	2	1				

Hump	hrey & St	tretton - S	Stretton H	Risk Assessment No.	RA013				
	Spindle	Moulder	ulder Location: Factory Area					Risk Assessment Issue No.	Issue 1
EMP	CON	PUB	VIS	Assessed By:	CG/DH/SH	Assessed on Site By:	CG/DH/SH	Duration of Task	Varies
1	0	0	0	Date of Assessment:	24.06.2020 Date of Site Assessment 24.06.2020			Review Cycle	Where circumstances dictate
	EMP	Spindle EMP CON 1 0	Spindle Moulder EMP CON PUB 1 0 0	Spindle Moulder EMP CON PUB VIS 1 0 0 0	Spindle Moulder Location: EMP CON PUB VIS Assessed By: 1 0 0 0 Date of Assessment:	Spindle Moulder Location: EMP CON PUB VIS Assessed By: CG/DH/SH 1 0 0 0 Date of Assessment: 24.06.2020	Spindle Moulder Location: Factory Area EMP CON PUB VIS Assessed By: CG/DH/SH Assessed on Site By: 1 0 0 0 Date of Assessment: 24.06.2020 Date of Site Assessment	EMP CON PUB VIS Assessed By: CG/DH/SH Assessed on Site By: CG/DH/SH 1 0 0 0 Date of Assessment: 24.06.2020 Date of Site Assessment 24.06.2020	Humphrey & Stretton - Stretton House, 20, Pindar Road, Hoddesdon, Herts - EN11 OEU No. Spindle Moulder Location: Factory Area Risk Assessment Issue No. EMP CON PUB VIS Assessed By: CG/DH/SH On Site By: 1 0 0 0 Date of Assessment: 24.06.2020 Date of Site Assessment 24.06.2020 Review Cycle

Code: Persons at Risk **EMP** – Employee **CON** – Contractor **PUB** – Public **VIS** – Visitor Without Controls With Controls Methods of Hazard monitoring Foreseeable Risks Control Measures Hazard RR Ref. RR S Ρ S Ρ control SxP No. SxP measures



Spindle Moulder

IF THE RISK RATING (RR) IS ABOVE 16 WORK WILL NOT BE ALLOWED TO PROCEED UNTIL CONTROL MEASURES ARE REVIEWED AND REDUCED

Risk Rating (RR) Severity (S) x Probability (P)

Low Risk = 1-8 Medium Risk = 9-15 High Risk 16-25

		Probability of Incident occurring								
		Frequent = 5	Likely = 4	Occasional = 3	Seldom = 2	Unlikely = 1				
	Fatality = 5	25	20	15	10	5				
> =	Major Injury = 4	20	16	12	8	4				
Severity Of Harm	Reportable to HSE = 3	15	12	9	6	3				
ŏδ	Minor Injury = 2	10	8	6	4	2				
	First Aid applied = 1	5	4	3	2	1				

Hump	hrey & St	tretton - S	Stretton H	Risk Assessment No.	RA013				
	Spindle	Moulder	ulder Location: Factory Area					Risk Assessment Issue No.	Issue 1
EMP	CON	PUB	VIS	Assessed By:	CG/DH/SH	Assessed on Site By:	CG/DH/SH	Duration of Task	Varies
1	0	0	0	Date of Assessment:	24.06.2020 Date of Site Assessment 24.06.2020			Review Cycle	Where circumstances dictate
	EMP	Spindle EMP CON 1 0	Spindle Moulder EMP CON PUB 1 0 0	Spindle Moulder EMP CON PUB VIS 1 0 0 0	Spindle Moulder Location: EMP CON PUB VIS Assessed By: 1 0 0 0 Date of Assessment:	Spindle Moulder Location: EMP CON PUB VIS Assessed By: CG/DH/SH 1 0 0 0 Date of Assessment: 24.06.2020	Spindle Moulder Location: Factory Area EMP CON PUB VIS Assessed By: CG/DH/SH Assessed on Site By: 1 0 0 0 Date of Assessment: 24.06.2020 Date of Site Assessment	EMP CON PUB VIS Assessed By: CG/DH/SH Assessed on Site By: CG/DH/SH 1 0 0 0 Date of Assessment: 24.06.2020 Date of Site Assessment 24.06.2020	Humphrey & Stretton - Stretton House, 20, Pindar Road, Hoddesdon, Herts - EN11 OEU No. Spindle Moulder Location: Factory Area Risk Assessment Issue No. EMP CON PUB VIS Assessed By: CG/DH/SH On Site By: 1 0 0 0 Date of Assessment: 24.06.2020 Date of Site Assessment 24.06.2020 Review Cycle

Code: Persons at Risk **EMP** – Employee **CON** – Contractor **PUB** – Public **VIS** – Visitor Without Controls With Controls Methods of Hazard monitoring Foreseeable Risks Control Measures Hazard RR Ref. RR S Ρ S Ρ control SxP No. SxP measures



SPINDLE MOULDER

SIGNING ON REGISTER

PERSONS IN ATTENDANCE DURING THE WORK- declaration

I, the undersigned, have read discussed and fully understand the above R.A.M.S. (Risk Assessment on the **SPINDLE MOULDER** and will adhere to all its method of working and conditions set down.

PRINT NAME	SIGNATURE	DATE

NOTE: -

All personnel in the work party must read, agree and sign the above prior to commencing the work.

If during the course of the work there are any changes to the method of work, the work must **stop** and a new R.A.M.S. produced in line with the method / conditions of work.