

Only complete the information required in the 6 yellow boxes below

ACTIVITY:

Using the Router - This process is 1 minute per cycle. However many breaks will occur during this task, it is highly unlikely that the EAV daily action level of 2.5 m/s<sup>2</sup> will every be exceeded. So no additional control measures are required at the present time. Worse scenario 10 total minutes per day. (20 Doors per day)

Power Tool in use (Detail make and model)

MAKITA RTO 700C ROUTER

Vibration magnitude m/s<sup>2</sup> r.m.s

3.5

Estimated trigger time per single operation (Sec)

60

Quantity of operations allowed per shift

1

Trigger time in minutes 1 = 0 Hours 0.50 Minutes

CONTROL BOX COLOUR KEY

- Adjust the quantity of operations allowed until all 4 control boxes show a green result (below the daily and total action values)
- Where the number of operations results in an orange control box (between the lower and upper exposure levels) then the control measures identified must be followed.
- Where a red control box occurs then the action levels have been exceeded and cannot be accepted.

VIBRATION CONTROL BOXES (Both apply)

		DAILY VIBRATION ACTION LEVELS	
		Daily	Total
EAV - Exposure Action Value	EAV	2.5	100
ELV - Exposure Limit Value	ELV	5	400

Daily exposure m/s <sup>2</sup> A (8)	Total Exposure points
0.11	0

CONTROL MEASURES : Control measures are not required as long as the quantity of operations is not exceeded

VIBRATION EXPOSURE POINTS READY RECKONER

VIBRATION MAGNITUDE m/s <sup>2</sup>	DAILY EXPOSURE TIME										
	15m	30m	1h	2h	3h	4h	4h	5h	8H	8h	10h
40	800										
30	450	900									
25	315	625	1250								
20	200	400	800								
19	180	360	720	1450							
18	160	325	650	1300							
17	145	290	580	1150							
16	130	255	510	1000							
15	115	225	450	900	1350						
14	98	195	390	785	1200						
13	85	170	340	675	1000	1350					
12	72	145	290	575	865	1150	1450				
11	61	120	240	485	725	970	1200	1450			
10	50	100	200	400	600	800	1000	1200			
9	41	81	160	325	485	650	810	970	1300		
8	32	64	130	255	385	510	640	770	1000	1200	
7	25	49	98	195	295	390	490	590	785	865	
6	18	36	72	145	215	290	360	430	575	720	
5.5	15	30	61	120	180	240	305	365	485	605	
5	13	25	50	100	150	200	250	300	400	500	
4.5	10	20	41	81	120	160	205	245	325	405	
4	8	16	32	64	96	130	160	190	255	320	
3.5	6	12	25	49	74	95	125	145	195	245	
3	5	9	18	36	54	72	90	110	145	180	
2.5	3	6	13	25	38	50	63	75	100	125	
2	2	4	8	16	24	32	40	48	64	80	
1.5	1	2	5	9	14	18	23	27	36	45	
1	1	1	2	4	6	8	10	12	16	20	